

Frontlit PVC Banner 450



Datum: 1 juni 2018



High quality PVC Banner with high tear resistance and durability for indoor and outdoor applications

FEATURES AND BENEFITS

- Fire rated to B1 certification
- Suitable for indoor and outdoor use
- Premium grade product
- Available up to 3.2m and 5.0m widths

Suitable for use with:



TECHNICAL SPECIFICATIONS

Properties	Test Method	Result	Unit
Total Weight	DIN53352 BS3424	450	g/sq.m
Tensile Strength (W/F)	DIN 53354 BS3424	2090.1/1867.4	N/5cm
Tear Resistance (W/F)	DIN 53356 BS3424	309.8/293.2	N/5cm
Opacity (%)/Transmittence		99	%
Welding Adhesion	DIN 53357 BS3425	80	N/5cm
Temperature Resistance	DIN 53372 BS3424	-20 - +70	°C
Max Width	DIN EN ISO 2286-1	5.0	Meter
Flame Retardant	NFPA-701, DIN4102-B1	B1	
Peeling Strength		42	N/5cm

All technical information and data above mentioned are provided to the best of our knowledge on the basis of our practical experience. They are offered in good faith, but without guarantee, as conditions and methods of use of our products are beyond our control. Therefore we can make no warranties, expressed or implied, including, but not limited to any implied warranty of merchantability or fitness for a particular purpose. We recommend that the prospective user determine the suitability of our materials and suggestions before adopting them on a commercial scale. The user is responsible for determining whether the product is fit for a particular purpose and suitable for the user's method of application.